

i400MAX Quick Start Guide

SHENZHEN VIDENT TECHNOLOGY CO., LTD Copyright ©2025 Vident Tech.



1. Registration and Software Upgrade

- 1. VIDENT Diagnostic APP started automatically: click UPDATE options to start product registrations in the lower left corner.
- 2. Vident account Registration: Enter the relevant personal information, after the input is complete, click "submit" to complete the account registration.
- 3. Upgrade Diagnostic Software: Enter the software downloading page, click ★ icon to start the download. Once the download is completed, the software package is automatically installed. Click II icon to cancel the downloading.









2. Connecting to Vehicles

- 1. Preparing for vehicle diagnosis:
 - 1) Turn on the ignition switch;
 - 2) The car battery voltage should be 11-14V.
- 2. Find the location of vehicles diagnostic socket: For passenger vehicles, most of the diagnostic sockets are standard OBDII 16-pin, generally installed under the dashboard. It is not excluded that some vehicles are located in other locations due to special design.

3. Connection:

- 1) For vehicles equipped with OBDII diagnostic socket, directly insert the VCI diagnostic connector into the vehicle diagnostic socket or use an OBDII extension cable to connect the VCI diagnostic socket to the vehicle diagnostic socket.
- 2) For vehicles equipped with non-OBDII diagnostic sockets, first select the corresponding adapter from the non-standard package and transfer it to the OBDII-16-pin diagnostic connector for connections.

Disclaimer: All pictures in this quick use manual are for reference only, please refer to the actual product. Vident reserves the rights to modify this quick use manual without notice. For more detailed operations, please contact local distributor or VIDENT company directly.

If you encounter any problems during the operation of the device, please email support@videnttech.com for assistance.



General Notice

For your own safety and the safety of others, and to prevent damage to the equipment and vehicles, read this guide thoroughly before operating your scan tool. The safety messages presented below and throughout this user's manual are reminders to the operator to exercise extreme care when using this device. Always refer to and follow safety messages and test procedures provided by vehicle manufacturer. Read, understand and follow all safety messages and instructions in this manual.

Safety Precautions and Warnings

To prevent personal injury or damage to vehicles and/or the scan tool, read this instruction manual first and observe the following safety precautions at a minimum whenever working on a vehicle: Always perform automotive testing in a safe environment. Wear safety eye protection that meets ANSI standards. Keep clothing, hair, hands, tools, test equipment, etc. away from all moving or hot engine parts. Operate the vehicle in a well-ventilated work area: Exhaust gases are poisonous. Put blocks in front of the drive wheels and never leave the vehicle unattended while running tests. Use extreme caution when working around the ignition coil, distributor cap, ignition wires and spark plugs. These components create hazardous voltages when the engine is running. Put the transmission in PARK (for automatic transmission) or NEUTRAL (for manual transmission) and make sure the parking brake is engaged. Keep a fire extinguisher suitable for gasoline/chemical/ electrical fires nearby. Ignition is on or the engine is running. Keep the scan tool dry, clean, free from oil/water or grease. Use a mild detergent on a clean cloth to clean the outside of the scan tool, when necessary.

Warranty and Service Limited One Year Warranty

We warrants to its customers that this product will be free from all defects in materials and workmanship for a period of one (1) year from the date of the original purchase, subject to the following terms and conditions: 1) The sole responsibility of our company under the Warranty is limited to either the repair or, at the option of our company, replacement of the scan tool at no charge with Proof of Purchase. The sales receipt may be used for this purpose. 2) This warranty does not apply to damages caused by improper use, accident, flood, lightning, or if the product was altered or repaired. 3) We shall not be liable for any incidental or consequential damages arising from the use, misuse, or mounting of the scan tool. Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply to you. This warranty is provided in addition to any rights and remedies available to consumers under relevant consumer protection laws